

BACKGROUND INFO

SRP (USA; Canada): \$2,995; \$4,095
 Manufacturing Status: New
 Domestic Intro Date: February 2002
 OEM: Matsushita Graphic Comm. Sys. (Japan)
 Also Sold As: None

Compatibility: Group 3

**TYPE**

Market Position: High-volume
 Configuration: Desktop
 Scanning Method: CCD
 Print Method: Laser
 Coding System: MH/MR/MMR/JBIG

SPEED/RESOLUTION

Modem/Transmission Speed: 33.6 Kbps/3 spp
 Print/Quick Scan Speed: 10.2 ppm/0.9 spp
 Maximum TX Resolution: 406 x 391 lpi
 Gray Scale/Halftones: 64 levels

PAPER HANDLING

Paper Source: One drawer (adj)
 Paper Capacity: 500 sheets
 Max Paper Cap w/Options: 1,250 sheets
 Document Feeder: 70 sheets
 Max/Min Orig Size (WxL): 11 x 78.7/5.8 x 5
 Max Paper/Print Width: 8.5/8.2
 Effective Scanning Width: 9.9
 Correct-Order Output: Face up
 Output Trays:
 Originals: Side, horizontal
 Receptions: Side, horizontal

DIALING CAPABILITIES

One-Touch Dialing Keys: 40
 Speed-Dialing Codes: 160
 Max Numbers Stored: 200
 Redial Attempts/Intervals: Up to 15/1 to 15 minutes
 Group Dialing: 8 groups, 199 numbers
 Program Keys: 8

SECURITY CODES

Access/Closed User Group: Yes/Yes
 Department Codes: 24 codes

COPYING SPECIFICATIONS

Max Copy Speed: 10.2 cpm
 Max Copy Resolution: 400 x 400 dpi
 Zoom Range (%): 70% to 100%

FEATURES

Multi Access: Yes
 Dual Lines: Optional
 Transmission Reservation: Yes
 ECM: Yes
 Auto Fax/Tel Switch: No
 Polling/Location(s): Yes/270
 Verification Stamp: Standard
 Relay Req/Transfer Hub: No/No
 Timers: 70 timers
 Confidential TX/RX: Yes/20 mailboxes
 Other Features:

Smoothing; picture/text recognition; edit file mode; receive collation stack; check and call; remote diagnostics; fax forwarding; distinctive-ring detection; ITU-T subaddress tx; optional telephone handset (SRP: \$75)

MEMORY

Std/Max Capacity: 2 MB/10 MB
 Std/Max Page Capacity: 120 pages/760 pages
 Document Memory Backup: Standard, flash memory
 Memory Transmission: Instant dial-tx
 Batch Files: Up to 5 files
 Broadcasting: Sequential (270 dest)
 Substitute Reception: Yes
 Multicopy Quantity: 99 copies

ADDITIONAL INFORMATION

Dimensions (H x W x D): 12.2" x 17.3" x 17.7"
 Weight: 35.3 lbs.
 Power Requirements: 99-138 V, 5 A
 Power-Save Mode: 1.2 watts
 Warranty: 1 year*

COMMENTS

*Available through Panasonic's National Accounts Program

OPTIONS

2-MB (160 pp) fax memory: \$189
 4-MB (320 pp) fax memory: \$299
 8-MB (640 pp) fax memory: \$399
 Add'l 250-sheet feed unit: \$349
 Add'l 500-sheet feed unit: \$539
 33.6-Kbps dual-line option: \$849

SUPPLIES

Print cartridge: \$250/12,000

% COVERAGE

ITU-T #1

Info not avail = Info not provided by MFR. Specs were obtained from manufacturer/distributor and not confirmed by BLI testing.

MFP SPECS - 2

(FAD IMAGE #22047)

MULTIFUNCTION MODES

Copier: Std conven Network Printer: No
 Fax Machine: Std PC Printer: Std
 Internet Fax: No Network Scanner: No
 Network Fax: No PC Scanner: Std
 PC Fax: Std

CONNECTIVITY SPECIFICATIONS

Operating System Support: Win 9.x, Me, NT 4.0, 2000, XP
 Parallel Interface: Std
 PC Fax/Print/Scan: Yes/Yes/Yes
 Serial Interface: No
 PC Fax/Print/Scan: No/No/No
 USB Interface: No
 PC Fax/Print/Scan: No/No/No
 Network Interface: No
 Interface Type: No

 LAN Fax/Print/Scan No/No/No
 Networks Supported:
 NetWare: No
 Windows NT: No
 AppleTalk: No
 UNIX: No
 AS/400: No
 Other:

PC/NETWORK FAX SPECIFICATIONS

Modem Speed: 33.6 Kbps
 Software (Std or Opt): Std Panafax Desktop
 Program Fax Via PC: No
 RX to PC Memory: No
 RX w/PC Off: No
 Class 1-/2- Compatible: No/No
 Color Fax RX/TX: No/No
 LAN Fax Support: No
 Connection Type: No
 Type: No
 Internet Fax RX/TX: No/No
 Dial-up: No
 Network Connection: No
 Other:

Internet Service Provider: No
 Other:

PRINTER SPECIFICATIONS

Engine Mfr & Model: Matsushita**
 Print Speed (Black): 10.2 ppm
 Print Speed (Color): Not applicable
 Print Resolution (Black): 600 x 600 dpi***
 Print Resolution (Color): Not applicable
 Processor/Bits/MHZ: Info not avail
 PDL/PCL: Windows GDI, opt PCL 5 e/6
 Controller Manufacturer: Matsushita
 LAN Print Speed/Res: No/No
 Std/Max Memory: 2 MB/10 MB
 Other: **Engine model number not available
 ***600 dpi with opt D-RAM memory of 4 MB or larger

SCANNER AND IMAGE MANAGEMENT SPECIFICATIONS

Scan Speed (Black): 0.9 spp
 Scan Speed (Color): Not applicable
 Max Resolution (Black): 400 x 400 dpi
 Max Resolution (Color): Not applicable
 TWAIN/ISIS Compatible: Yes/No
 Scan/Image Software: Std Panafax Desktop

 OCR Software: Std Panafax Desktop
 File Mgmt Software: Std Panafax Desktop
 Scan-To-E-Mail: Std Panafax Desktop

Other: Scan-to-e-mail is accomplished through a direct parallel connection to a PC. The PC must be running a MAPI-compliant e-mail program

CONTENTS

Base unit; power cord; telephone line cord; autodial key labels; operation manual; receive paper tray; output paper tray; print cartridge; bundled Panafax Desktop software

COMMENTS**CONNECTIVITY OPTIONS**

PCL 5e/6 printer interface: \$679
 4-MB D-RAM printer memory: \$249
 8-MB D-RAM printer memory: \$299

Info not avail = Info not provided by MFR. Specs were obtained from manufacturer/distributor and not confirmed by BLI testing.

MFP SPECS - 3

(FAD IMAGE #22047)

©2003 Buyers Laboratory Inc., 20 Railroad Ave., Hackensack, NJ 07601; (201) 488-0404; Web Site: <http://www.buyerslab.com>